


# Installation Instructions

Please read through ALL of the instructions BEFORE YOU BEGIN.

Installation videos available at <https://www.photodon.com/Videos.html>

Unless noted, all screen protectors have 3 layers.

Photodon Screen Protector Film Structure



## 1. Install the test film

**A)** Install (as indicated in Step 3A) the enclosed test film to understand how the screen protector behaves and to see if the effect is desirable. Be sure to remove both liners.

**NOTE:** DO NOT OPEN your screen protector unless you are satisfied with the results of the test film.

**B)** If you are satisfied with the test film results, gently open your package.

**NOTE:** Blemishes or fingerprints that appear on the film are typically on the liners and do not affect the screen protector installation result.

**C)** Hold the screen protector up to your device to ensure it is a proper fit. Note the amount of gap around the edges between the screen protector and the bezel of your device for placement in step 3B.

## 2. Prepare for installation

**NOTE: DO NOT RUSH THIS STEP.** Dust particles between the screen protector and the screen create bubbles that will need to be dealt with later.

**A)** If possible, vacuum the screen and surrounding area using a soft, clean dusting brush. If not possible to use a vacuum, use a microfiber cloth to gently remove dust from the screen.

**B)** Clean the screen protector. To reduce static electricity, use Staticide wipe or spray on the screen protector and surrounding areas of the device. DO NOT use the staticide directly on the device screen.

**C)** Use a liberal amount of Screen/Lens Cleaner with a microfiber cloth to wipe the device screen, evenly distributing the cleaning solution. Rotate the cloth to use a dry portion to wipe the screen until the screen is dry.

## 3. Install the screen protector

**NOTE: DO NOT TOUCH** the film's adhesive backing. We recommend the use of rubber gloves to reduce the chance of introducing fingerprints on the adhesive layer.


**A)** Gently pull up on the protruding tab on the screen protector to begin removal of the back liner.

## Tips for a Successful Installation:

- Install screen protector in a dust-free, clean environment.
- Vacuum and wipe hard surfaces in the installation area.
- Avoid wearing linty clothing.
- Apply protector while device screen is turned off, cooled down and laid flat if possible.
- Get a second person for screen protectors 30" or larger if possible.
- Install protector where temperatures are above 60° F (16° C).



**B)** Pull the back liner, revealing 2-3 inches of the adhesive layer, and fold it under the protector as it separates. Place the protector on the screen parallel with the screen edge, centering the screen protector left to right or top to bottom, taking into account the gap size noticed in step 1C.



**C)** Using a finger, apply light pressure to the top side of the screen protector to seal it to your screen. If you observe an air bubble, it is OK to continue sealing the screen protector as it/they can be pushed out later (as indicated in Step 3E. Ensure the position of the screen protector remains aligned.

**IMPORTANT:** 1 or 2 bubbles can be left in place to fix later. Screen protector alignment is most important. If there are a number of bubbles present, the film may be gently lifted until the bubbles are gone then laid back down.



**D)** Continue to slowly pull the back liner allowing the screen protector to lay in place.

**Hint:** Placing tension on the screen protector or pulling the liner too fast can cause the formation of air bubbles.

As you near the end of the installation, remove the back liner completely and allow the screen protector to slowly lay in place.



**E)** Use the provided squeegee to push any air bubbles to the nearest edge of the screen protector.

**Hint:** If an air bubble has a dot in the center of it, this indicates dust or lint. If the top liner has not been removed, you can use a marker to circle the spot where the dust/lint is. Carefully lift the nearest corner of the screen protector and use the enclosed tacky tape to remove the particle. Let the screen protector lay back into place. Debris normally sticks to the silicone backing of the screen protector.



**F)** Carefully remove the front protective liner (identified with a tabbed sticker) by pulling up on it until it releases.

**G)** Using a finger, apply light pressure around the edges of the screen protector to seal it completely.

Congratulations! The installation is now complete! Clean and maintain your screen protector with regular screen cleaner.

Please contact us if you have any issues. We are here to help!  
847.377.1185 M-F 9-5 EST [sales@photodon.com](mailto:sales@photodon.com)

For additional information and helpful tips on film application, check the FAQs: <http://www.photodon.com/FAQ-Screen-Protectors.html>  
Installation videos: <https://www.photodon.com/Videos.html>

Visit **Photodon.com** for other Professional Screen Care Products  
Photodon LLC, Traverse City, Michigan USA

